



tilemaster adhesives

PROFESSIONAL FLOORING PRODUCTS

PRIMERS AND DAMP PROOF MEMBRANE



Prime + Grip

MULTI-PURPOSE BOND ENHANCING PRIMER

- Rapid drying 15 – 20 minutes
- Significantly improves adhesion bond strength of smoothing compounds
- Ideal for use on smooth, non-absorbent & absorbent surfaces
- Provides an excellent "+ Grip" surface
- Ready mixed & ready to use
- Single part, high strength – accepts Tilemaster leveller up to 50mm thick

Coverage: Approximately 45 – 65m² per 5kg
Drying Time Before Levelling:
15 – 20 minutes in ideal conditions
Pack size: 5kg



Primeplus

PRIMING AND BONDING AGENT

- Fast drying
- For absorbent & non-absorbent surfaces
- Designed to prime, stabilise & seal substrates
- Increases adhesion strength of smoothing compounds
- Prolongs the working time of smoothing compounds
- Reduces the risk of pin-holes forming
- SBR based primer

Coverage: 1 litre applied neat = 10m²
1 litre diluted with 3 parts water = 40m²
1 litre applied as a slurry coat = 18m²
Drying Time Before Levelling:
30 – 45 minutes in ideal conditions
Pack sizes: 1 Litre & 5 Litre bottles



Fast One Coat DPM

FAST CURING SURFACE DAMP PROOF MEMBRANE – EPOXY BASED

- Fast curing – ready to receive smoothing compounds in 4 – 5 hours
- 2 component, solvent free, One Coat DPM
- Suitable for use on surfaces with a moisture reading of up to 98% RH
- Can be installed where no structural DPM is present (2 coats)
- Suitable for use over underfloor heating systems
- Ideal for use on Anhydrite / Calcium Sulphate screeds
- Supplied in convenient easy to use packaging

Coverage: Approximately 22 – 25m² per 10kg
Working time: Approximately 20 – 25 minutes
Drying Time Before Levelling:
4 – 5 hours in ideal conditions
Pack size: 10kg & 3kg

2 PART / LATEX SMOOTHING COMPOUNDS



Trade Flow

MULTI-PURPOSE TWO PART SMOOTHING COMPOUND

- Excellent flow & levelling properties
- Apply from 2 – 12mm
- Light foot traffic after 2 hours
- Apply floor coverings after 12 hours
- Moisture tolerant
- Ideal for plywood overlay substrates & underfloor heating systems
- Low odour & protein free

Screed Classification: CT-C20-F6 to EN13813:2002
Open / Working time @ 20°C: 20 – 25 minutes
Time to foot traffic @ 20°C: 2 hours
Ready to cover: 12 hours
Coverage: A 20kg bag and 5L liquid unit will cover 5.0m² at 3mm thickness
Pack size: Bag - 20kg, Liquid - 5 Litres



Pro Flow

RAPID SETTING, HIGH PERFORMANCE TWO PART SMOOTHING COMPOUND

- Walk on after 90 minutes
- Install floor coverings after 4 hours
- Moisture tolerant – can be used below a DPM
- Excellent adhesion properties without priming most substrates
- Suitable for use over old adhesive residues including bitumen
- Apply from 2 – 12mm
- Low odour & protein free

Screed Classification: CT-C16-F7 to EN13813:2002
Open / Working time @ 20°C: 20 – 25 minutes
Time to foot traffic @ 20°C: 90 minutes
Ready to cover: 4 hours
Coverage: A 20kg bag and 5L liquid unit will cover 5.0m² at 3mm thickness
Pack size: Bag - 20kg, Liquid - 5 Litres



Super Flow 30

ULTRA-RAPID SETTING, HIGH PERFORMANCE TWO PART SMOOTHING COMPOUND

- Rapid drying, install floor coverings after 90 minutes
- Suitable for use over old adhesive residues including bitumen
- Moisture tolerant – can be used below a DPM
- Ideal for plywood overlay substrates
- Can be used above underfloor heating systems
- Provides a genuine fast track system when used in conjunction with Fast One Coat DPM
- Low odour & protein free

Screed Classification: CT-C16-F6 to EN13813:2002
Open / Working time @ 20°C: 10 – 15 minutes
Time to foot traffic @ 20°C: 30 minutes
Ready to cover: 90 minutes
Coverage: A 20kg bag and 4.5L liquid will cover 4.5m² at 3mm thickness
Pack size: Bag - 20kg, Liquid - 4.5 Litres

REPAIR MORTAR & FEATHER FINISH



Rapid Repair Mortar

RAPID REPAIR MORTAR FOR INTERNAL WALLS AND FLOORS

- Ideal for repairing, re-facing, filling and patching internal concrete, sand / cement screeds, render, stair-treads, ceilings, soffits and forming ramps
- Apply from 2mm – 20mm unfilled and 5mm – 50mm when mixed with aggregate
- Apply finished flooring after 90 minutes
- Slump free, ideal for horizontal and vertical applications
- Protein free

Screed Classification: CT-C30-F7 to EN13813:2002
Open / Working time @ 20°C: Approximately 10 – 15 mins
Time to foot traffic @ 20°C: Approximately 30 – 40 mins
Ready to cover: 90 minutes
Coverage: 11kg will cover 7m² at 1mm thickness
Pack size: Bag - 11kg



Tilemaster Feather

RAPID DRYING PATCH REPAIR AND SMOOTHING COMPOUND

- Rapid drying, floor coverings can be applied after as little as 15 minutes
- Ideal for use on timber substrates
- Suitable for use above underfloor heating systems
- No need to prime
- Excellent adhesion properties
- Coverage of 50m² per 11kg bag
- Simply mix with water
- Protein free

Screed Classification: CT-C12-F5 to EN 13813:2002
Open / Working time @ 20°C: Approximately 15 minutes
Ready to cover: 15 minutes
Coverage: When mixed with 6L of water and applied as a scrape coat, an 11kg bag of Tilemaster Feather will cover approximately 50m² (approximately 10m² at a 1mm depth)
Pack size: Bag - 11kg



Fine Flow 3000

EXCEPTIONAL FLOWING & SMOOTHING – HEAVY DUTY SELF LEVELLING FLOOR COMPOUND

- Excellent levelling & smoothing properties
- Apply from 2 – 20mm
- Foot traffic after 3 hours
- Install floor coverings after 24 hours
- Ideal for underfloor heating systems
- Protein free

Screed Classification:
CT-C30-F7 to EN 13813:2002
Open / Working time @ 20°C: 20 – 30 minutes
Time to foot traffic @ 20°C: 2 – 3 hours
Ready to cover: 24 hours
Coverage: 20kg will cover 4.2m² at 3mm thickness
Pack size: Bag - 20kg

WATER BASED SMOOTHING COMPOUNDS



Levelflex

FLEXIBLE & FIBRE REINFORCED, RAPID SETTING SELF LEVELLING FLOOR COMPOUND

- Ideal for plywood overlay substrates
- Apply directly to T & G floorboards
- Apply from 2 – 50mm
- Ideal for underfloor heating systems
- Foot traffic after 3 hours
- Install floor coverings after 24 hours
- Fibre reinforced & shrinkage compensated
- Protein free

Screed Classification:
CT-C30-F7 to EN 13813:2002
Open / Working time @ 20°C: 20 – 30 minutes
Time to foot traffic @ 20°C: 2 – 3 hours
Ready to cover: 24 hours
Coverage: 20kg will cover 4.2m² at 3mm thickness
Pack size: Bag - 20kg



Rapid Level 30

ULTRA – RAPID SETTING, FLEXIBLE, SELF LEVELLING FLOOR COMPOUND

- Foot traffic after 30 minutes
- Install floor coverings after 90 minutes
- Apply from 2 – 15mm
- Ideal for plywood overlay substrates
- Ideal for underfloor heating systems
- Excellent levelling & smoothing properties
- Protein free

Screed Classification:
CT-C35-F10 to EN 13813:2002
Open / Working time @ 20°C: 10 – 15 minutes
Time to foot traffic @ 20°C: 10 – 15 minutes
Ready to cover: 90 minutes
Coverage: 20kg will cover 4.2m² at 3mm thickness
Pack size: Bag - 20kg



AnhyLevel

GYPSUM BASED, FLEXIBLE SELF LEVELLING FLOOR COMPOUND

- Developed specially for application to anhydrite & calcium sulphate screeds
- Ideal for underfloor heating systems
- Apply from 2 – 20mm in one application
- Fast drying - light foot traffic after 3 hours
- 100% compatible with gypsum based substrates
- Excellent self levelling properties
- Protein free

Screed Classification:
CA-C30-F10 to EN 13813:2002
Open / Working time @ 20°C: 20 – 30 minutes
Time to foot traffic @ 20°C: 2 – 3 hours
Ready to cover: 24 hours
Coverage: 20kg will cover 4.2m² at 3mm thickness
Pack size: Bag - 20kg