# BREMIUM PORCELAIN **FREMIUM PORCELAIN FREMIUM PORCELAIN**

# New Collection 2021 - 2022

A PAR

### **Design Inspiration**

1916

Get inspired and learn how to create the perfect space to relax, entertain and enjoy

### Accessories

Everything you need to install your outdoor porcelain tiles to the highest standard.

### Installation Advice

Our simple guide shows you the many ways you can install outdoor porcelain tiles.

#### www.alfrescotiles.co.uk

# Extend your home to the great outdoors...

Our premium porcelain Al Fresco range features 10mm tiles for indoor use and 20mm tiles for outdoor use to create seamless open plan living spaces. Our premium porcelain outdoor tiles offer a stylish alternative to stone or concrete flagstones and our wood effect range creates the look of high-end timber decking but with many added benefits such as good slip resistance. Hard wearing and practical, these tiles have a 10 year guarantee, are simple to install and require no sealing - the perfect way to create a durable and low maintenance living space that's great for the whole family.

# Feature & Benefits

Not only do Al Fresco indoor and outdoor tiles look amazing, they also have many other benefits. Tiles have been used within the home for decades to create amazing spaces, why not extend that to the great outdoors? Al Fresco tiles are manufactured in a way that avoids all imperfections associated with natural stone and traditional paving slabs. Pressed in a raw state and heated at very high temperatures, Al Fresco tiles are stylish, strong and durable.





#### **Uniform Thickness**

Al Fresco tiles are manufactured under extremely tight tolerances ensuring an even thickness and stable surface every time. They also feature precision cut rectified edges for a premium finish every time.



#### Algae & Moss Resistant

Unlike natural materials such as stone or timber, our outdoor Al Fresco tiles are resistant to algae and moss - no need to worry about your tiles turning green and becoming slippery!



#### Good Slip Resistance

Al Fresco tiles have a good slip rating of R11 making them safe and practical in all weather conditions. For more information on slip ratings, see page XX.







#### Simple to Install

Create a traditional patio, or loose lay outdoor porcelain tiles onto grass, gravel or sand without the need for any specialist installation equipment. If you already have a solid surface, why not try our pedestal installation system? For further installation advice, see page XX.











#### Frostproof

Natural stone and timber is porous and allows water to enter the surface. When this freezes, this can crack the material. Durable under extreme tempreratures, Al Fresco porcelain is completely frostproof.



#### Easy to Clean

Al Fresco outdoor porcelain tiles are extremely low maintenance. To clean, simply brush with a mix of washing up liquid and water. For more stubborn stains, use Al Fresco residue remover, see page XX.



#### **Colour Bodied**

Sometimes, accidents happen - but don't worry! The core of our Al Fresco outdoor porcelain tiles are colour bodied, meaning that any unfortunate small chips that may occur will barely be noticeable.



#### **Fade Resistant**

Perfect for sunny spots, Al Fresco tiles are created using high definition printing techniques with inks that will not fade or lose their colour.





# **Abbey Black Multi**

Create an authentic look in a classic black and multi-shade slate effect design with a look of natural stone but in a low maintenance tile that won't fade or deteriorate, whatever the British weather may bring. Each tile features a varied mix of black and natural shades that are indistinguishable from real slate making it a practical and low maintenance option for a variety of outdoor spaces. Remember to always mix up your tiles prior to fixing to create a pleasing blend of shades.

Available in size 600x600x20mm outdoor See specification table on page 35 for more information

Featuring a softer blend of shades than Abbey Black Multi, Newby Grey Multi is perfect for creating a relaxing and rustic outdoor space. Each tile features a unique blend of soft grey and natural shades , carefully crafted from durable porcelain to look just like natural stone but without the need for sealing or excessive maintenance. Relax and enjoy your time outdoors to create a pleasing blend of shades.



Available in size 600x600x20mm outdoor See specification table on page 35 for more information

The Chatsworth collection features a subtley shaded pattern with tonal flecks of stone effect detailing. Opt for the contemporary and versatile Light Grey shade, or create a bolder statement with the striking Dark Grey shade that really makes plants and foliage pop. For a softer and more natural look the lvory shade is perfect for creating a relaxed and clam feel. Frost and fade resistant, these tiles are a practical choice for any outdoor space.

lvory, Light Grey & Dark Grey available in sizes 600x600x20mm & 600x900x20mm outdoor See specification table on page 35 for more information







### Chatsworth





has been created using high definition priniting techniques that create a look of natural stone, but without the need for sealing and maintenance. Exbury is available in two shades - modern classic Grey, and traditional warming Beige. Coordinate 10mm thick tiles through to your interior spaces too for a seamless finish from garden to home.

Beige & Grey available in sizes 595x595x10mm indoor, 600x600x20mm outdoor & 600x900x20mm outdoor See specification table on page 35 for more information





# Harewood

If you love the look of natural wood or timber decking, then Harewood is the perfect collection to create a hard wearing and durable patio area. Unlike timber, our porcelain tiles do not require sealing to protect them and will not rot or become slippery in wet weather. Contemporary Grey creates a cool and stylish space, whilst the Oak shade grounds gardens and offers natural charm. Our indoor 11mm thick tiles come in a slightly smaller format to better suit indoor spaces and blur the boundaries between indoor and outdoor living.

Grey & Oak available in sizes 195x1200x11mm indoor & 300x1200x20mm outdoor See specification table on page 35 for more information









Easy to install in a variety ways including onto sand, grass or gravel, Harlow brings natural warmth to your outdoor space. The Harlow collection features a subtly textured surface and gentle mottling detail which enhances the realistic stone nature. Harlow works harmoniously with an array of exterior styles and is available in warm and inviting Beige and stylish Grey. Combine both 600x600mm and 600x900mm sizes together for an organic and modular effect that will look beautiful for years to come.

### Harlow

Beige & Grey available in sizes 600x600x20mm & 600x900x20mm outdoor See specification table on page 35 for more information

# **Adlington White**

Adlington features a fresh and light white colouring mixed with traces of natural tones that's ideal for creating an illusion of space in small gardens. Coordinate with bright pops of colour and a mixture of florals for a bright and exciting space, or for a more traditional mediterranean look add terracotta pots and deep aqua blue tones reminiscent of the sea and summer sky. Fade resistant in strong sunlight and resistant to algae and moss, Adlington will look perfect for many years to come.

Available in size 600x600x20mm outdoor See specification table on page 35 for more information



In stark contrast to Adlington, Sherborne is the darkest shaded tile in the Al Fresco collection featuring a striking black tone with a subtle stone effect pattern. The deep shading of this tile creates the ideal backdrop to allow plants and foliage to pop with colour. Style with shades of grey and white for an ultra-sleek monochrome look that's both hardwearing and low maintenance.





## **Sherborne Graphite**

Available in size 600x600x20mm outdoor See specification table on page 35 for more information





Create a striking and unique look with a look of natural stone but in a low maintenance tile that won't fade over time. Each tile features a varied mix of natural patterningm and stone-style veining that replicates the real thing. Rosemoor is available in two shades - soft and calming grey, and warm and inviting sand. Remember to always mix up your tiles prior to fixing to create a pleasing blend of patterns and shades.

### Rosemoor

Sand & Grey available in size 600x900x20mm outdoor See specification table on page 35 for more information

# Welford

Add a contemporary touch to your outside space with the subtle concrete style patterning of Welford. This modern design has been created using high definition priniting techniques that create a look of weathered stone, but without the need for sealing and maintenance. Welford is available in three shades - dark and moody Anthracite, classic and chic Grey, and warm and inviting lvory. Coordinate 10mm thick tiles through to your interior spaces too for a seamless finish from garden to home.

lvory, Grey & Anthracite available in sizes 595x595x10mm indoor & 600x600x20mm outdoor See specification table on page 35 for more information









# Welford Geometric

Looking for something a little bit different? Our Welford Geometric tiles are the perfect choice to create a unique outdoor living area. Embrace the great outdoors and create a feature floor that is sure to get your friends and family talking. Combine with Welford non-patterned tiles to create zoned areas - ideal for defining entertaining and relaxing spaces. Extremely hard wearing and simple to install, Welford Geometric tiles are the easy way to create a statement on-trend outdoor space.

> Grey Geometric & Anthracite Geometric available in size 600x600x20mm outdoor See specification table on page 35 for more information



# **Installation Accessories**

From small and intimate patios, to large scale landscaping projects, the AI Fresco collection offers a comprehensive range of installation accessories to perfect any project. If you are fixing your tiles with mortar, Instarmac Pro-Prime Slurry is an absolute essential to ensure your tiles bond to the base below. Use AI Fresco Tile Protector to create a protective seal against installation residues such as mortar and grouting compounds and for any stubborn stains after installation, use the Al Fresco Residue Remover. For a perfect finish, Instarmac ProPave Brush-In Grout infills joints with minimal effort. An alternative installation method is our pedestal support system which creates an elevated patio area without the need for lots of equipment. It can also be easily moved around or adjusted as the tiles are not fixed with adhesive.



### **Slurry Primer**

- Provides an exceptional bond between outdoor porcelain tiles and a wet mortar bed
- Just add water on-site



- 20kg paper bag covers 15sqm\*
- NBS Plus registered
- BS 7533 compliant

Al Fristo Porcelain





• Apply before grouting to create a protective seal against cement, grout & jointing compounds

ULTRA

slurry primer

pro-prime

- Apply after grouting to protect both exterior and interior porcelain tiles against the dirt of everyday living
- 1 Litre covers approx 25m<sup>2\*</sup>

### **Residue Remover**

- Rapid action cleaner for removing cement residues, grout stain and other similar deposits
- Suitable for exterior porcelain and also interior porcelain
- and residues
- 1 Litre covers approx 25m<sup>2\*</sup>

Coverage is provided as a guide only and reflects typical application without any wastage. It should ot be used as an exact material calculation

### **Brush-in Grout**

- Use to fill the gaps between tiles for a seamless finish
- Fast and easy application
- Walk on in just 24 48 hours
- Use in all weather
- Resistant to frost and extreme weather conditions
- 15kg tub covers up to 25sqm\*\*









Small Pedestal Medium Pedestal Height 60-105mm



leight 25-37mm



Corner Clips







Large Pedestal



Adjustment Key

### Pedestals

- Create a patio without the need for lots of equipment
- Pedestals allow for drainage and you can hide cables and equipment underneath
- As the tiles are not attached with adhesive, you can easily move them around
- Can be laid over any solid surface such as patios, concrete or balconies
- Self levelling pedestal head creates a stable surface on uneven ground
- Create a clean step front to raised patios using the edge &corner clips
- Easily adjust the patio level using the adjustment key

# **Design Inspiration**

When it comes to laying tiles in your garden, many people choose a regular grid of square or rectangular slabs, all the same size and colour. It's surprisingly easy to create a practical yet beautiful space by playing with different textures, colours and patterns. Here are some simple yet creative ideas to inspire you and help you to design your perfect space.



**Stack Bond** 



Third Bond







Herringbone



Modular-Style



**Random Stagger** 



Brick Bond

**Stack bond** is the simplest and most common way to lay a patio. Coordinate your grout colour for a seamless look, or use a contrasting colour to add a simple statement. Third bond is a great way to lay planks and larger tiles for a contemporary look. Staggering the tiles in this way creates an organic feel and helps to define the tiles shape. You can create an interesting twist on a simple pattern with the **diamond** layout - perfect for square tiles. Using a **random** stagger is a great way to create a natural look and the herringbone pattern is a good way to create a sense of space in small areas - both of these layouts work especially well for planks. Some of our Al Fresco collection features both square and rectangle tiles in the same design and colour - you can mix these together in rows to create a **modular-style** effect which is really effective in larger spaces. Larger porcelain tiles inherently have a slight curvature to them, which means that fixing them in a **brick bond** layout can make the floor appear slightly uneven. Although we don't recommend it, if you try laying your tiles in a brick bond pattern and you're happy with the level of evenness between each row of tiles then there's no reason why you can't lay them in this way.

27

# **Installation Advice**

With the right materials and preparation, you can easily install your own Al Fresco tiles. Follow these simple steps to create your own seamless indoor & outdoor space. Installing your own Al Fresco tiles is both rewarding and satisfying but you could be exposed to various risks if the correct safe methods of work are not followed. Before you begin, be sure you have the correct tools and the appropriate protective equipment. Always wear gloves and safety footwear when working with outdoor porcelain tiles. Handle your tiles with care to avoid breakages and seek assistance if needed when lifting.

### How to install a porcelain patio on wet mortar



#### Step One

Firstly, mark out the area where you want your patio to be with posts and string. Measure the length and width of your area and multiply these values together to calculate the square meterage. If your area is not a straight forward square or rectangle, break each area down into smaller rectangles. Calculate each rectangle, then add these values together. Once you've calculated the total square meterage, multiply this number by 1.1. This adds 10% extra on to your total to allow for cuts and wastage.



#### **Step Two**

Although outdoor porcelain tiles don't need to be sealed to protect them from water penetration, you may find the installation process easier if you coat the tiles before installation with Al Fresco Tile Protector. This prevents mortar and slurry from becoming ingrained in the surface of the tiles and makes cleaning up after installation even easier, though this is entirely optional. Apply to the surface of the tile with a foam roller, taking care not to coat the edges.



#### **Step Three**

Before you lay your tiles, you will need to prepare the ground, by digging to a depth of around 150-200mm. Your ground should have a slight slope to allow for drainage.



#### **Step Five**

Add a layer of mortar on top of the compressed hardcore. We recommend 4 parts sand to 1 part cement.



#### Step Six

Place 7 litres of clean water in a suitable container. Add UltraScape Pro-Prime powder slowly and mix for 3 to 5 minutes to create a smooth lump-free slurry. Coat the underside of the first tile with priming slurry.



#### **Step Seven**

Place the tile into position, using a corner as a starting point - for example next to a wall or the house. Press into place and use a rubber mallet and spirit level to secure and adjust the level, remembering to take drainage into consideration. Continue to lay tiles in this way leaving a 3-5mm gap between each one. Use a bucket and sponge to clean up any mortar or slurry as you go.



Scan here with your smart phone to view all our detailed installation videos



#### **Step Four**

Fill with hardcore (gravel and crushed hard rock) to a depth of 100-150mm and use a rake to distribute the mixture. Compress the hardcore using a whacker power plate, building up in layers. Remember to check that your ground still has a slight slope.



#### **Step Eight**

If you wish to infil any joint gaps, we recommend using ProPave brush-in grout designed for outdoor porcelain tiles. Use a brush to mix over the joints, gradually and evenly filling them all in. Once the joints are filled, use a pointing trowel to firm the grout into place. Add more grout if needed to create a clean and level finish.

### How to create a raised patio with pedestals



#### **Step One**

Pedestals are a great way to create a patio area without the need for lots of messy equipment or tools. They can be laid on top of any solid surface such as existing patios, tarmac driveways or even balconies. It's a good idea to lay a layer of weed membrane down under the pedestals so that you don't get weeds growing up through the cracks. If your sub-surface is completely solid such as a concrete slab or balcony, you can skip this step. If you don't already have a solid sub-base, you will need to create one before you begin installation.



#### **Step Two**

Before you begin, you will need to calculate how many pedestals you need. The easiest way to do this, is to measure and sketch out your patio plans. Each tile requires one pedestal in each corner. The spacer tabs in the top of the pedestal head hold the tile corners in place. For edges and corners, you will need to remove some or all of the spacer tabs so that the tile sits flush on top. For larger tiles you may wish to place an additional pedestal without spacer tabs in the centre for extra support.



#### **Step Three**

Prepare your pedestals for the edges and corners. For the edges, cut along the base line to remove one side. For the corners, cut along an additional base line to remove two sides and create a right angle.



#### **Step Five**

Continue to lay your tiles, adjusting the height and level as you go by inserting the adjustment key between the tile joints and twisting. Once the whole pedestal patio area is complete, review the level again and adjust if needed.



#### **Step Six**

If you need to create a step front, measure and cut your tile to the correct height (see page XX for cutting advice). Temporarily remove any tiles from the main patio area that lay on top of an edge or corner and prepare the edging clips by laying one piece underneath the pedestal, and one piece on top. The top piece should slot on top of the spacer tabs.



#### **Step Seven**

Place the cut tile piece in between the clips to hold it in place. If you wish, you can secure the edging clips with silicone or glue but this is not essential. Repeat this process for the corner clips until your step front is completed.



#### **Step Four**

Use a corner as a starting point such as next to a wall, house or fence, and place the first pedestal. Place three more pedestals in a grid layout to fit the measurements of your tile. Twist the pedestal by hand or with the adjustment key to alter the height. Align the pedestal head so that the cross shaped keyhole is at a right angle to the tile corner. Place the tile on top of the pedestals ensuring that the corners sit flush into the tabs.



#### Step Eight

Place your tiles back in place on top of the pedestals to complete the look.





### How to cut outdoor porcelain tiles



#### **Step One**

Outdoor porcelain tiles are super strong and cannot be cut using traditional hand tools. In order to minimise breakages and spoiled cuts, we recommend using a water fed cutter with a diamond blade. This will also help to minimise dust. Always wear gloves, safety footwear, goggles & respiratory protection when using cutting equipment. Handle your tiles with care to avoid breakages and seek assistance if needed when lifting.



#### **Step Two**

cut the tile. Cut from the top surface with the blade running at half-revs. Bring the blade into contact with the tile. As the blade bites the tile, increase the revs if necessary and progress along the marked line. Ensure the blade is water fed throughout and remains evenly balanced. Do not attempt to plunge the blade throught the tile in one go - progress steadily and repeat the process until the tile is cut.

### How to lay stepping stones or staggered patios



#### Step One

It's easy to create walkways and staggered patios by loose laying your outdoor tiles. If your surface is solid and secure, outdoor porcelain tiles can be simply placed on the ground.



#### Step Two

If the ground is soft or uneven in any way, you will need with a layer of sharp sand or fine gravel, then place your tile on top.

# **Important Information**

Although we have made every effort to display the colours accurately, we cannot guarantee that this printed brochure directly reflects the colours of the actual product. As products can vary slightly from these images, we advise you to order a sample for true colour representation. Please note that tiles are created in batches and some shade variation may occur between batches. Products with the same colour name, such as "grey", are not necessarily the same exact colour shade as another product with "grey" in its name. Please do not order using colour names or product names as your guide to colour. We manufacture our tiles to extremely tight tolerances, however due to the nature of the manufacturing process, sizes, weights, capacities, dimensions and measurements indicated may vary slightly.

Installing your own AI Fresco tiles is both rewarding and satisfying but you could be exposed to various risks if the correct safe methods of work as described in this booklet are not followed. Before you begin, be sure you have the appropriate protective equipment.

> • Always wear goggles & respiratory protection when using cutting equipment. require assistance when lifting.

• Handle your AI Fresco tiles with care to avoid breakages and chipping that may result from mishandling. • Larger tiles may

We take care to ensure that all of our Goods leave us in perfect condition. All orders must be examined on delivery and any shortages, damages or other discrepancies should be brought to the supplier's attention before installation. Confirm that all products have been inspected and approved before installation begins, as the installation of the product signifies acceptance.

Use Al Fresco Tile Protector to protect surfaces against staining from cement, grout and jointing compounds during the installation process. To keep your tiles looking their best, sweep the surface to clear away dust, dirt and debris. Fill a bucket with warm soapy water. Washing up liquid will work fine – do not use acid based or abrasive cleaning products. Wet a scrubbing brush with the soapy water and scrub the surface of the tiles until clean. Leave to dry naturally. For tougher stains or residues such as cement and grout stain, use Al Fresco Residue Remover.

Al Fresco tiles have a 10 year structural guarantee. We warrant that the structural integrity of the product will not fail, under normal conditions, within a period of 10 years from date of purchase. Because specific installation details structural design and environmental conditions are beyond the control of the Company, we cannot accept responsibility latent defects in the product caused by improper manufacturing, the Company will replace any defective product, provided the Company is notified in writing. The Company will also not be responsible if tiles are installed with a visible defect. The Company must pre-approve the cost of the replacement, in writing, prior to commencement of any warranty work.

R Ratings are determined via testing in accordance with DIN 51130:2004, which is the "Testing of floor coverings; determination of the anti-slip properties; workrooms and fields of activities with slip danger; walking method; ramp test German National standard 2004". This is fully recognised and adopted in the UK. The "R" values range from R9, which has a small degree of slip resistance, up to R13 which is the highest slip resistance. R9 & R10 ratings are suitable for indoor domestic areas, wheres R11 ratings and above are also suitable for external applications.

### Aftercare & Maintenance

Maintaining your porcelain tiles is easy, simply sweep away any loose dirt regularly, and brush with warm soapy water for an extra clean as and when needed. Outdoor porcelain tiles do not require sealing, however you may wish to apply Al Fresco Tile Protector after grouting to protect your tiles against the dirt of everyday living. For any mild stains and residues, dilute 1 part Al Fresco Residue Remover in 4 parts water. Dampen a cloth or sponge and wipe thoroughly. For tougher stains and residues, dilute 1 part Al Fresco Residue Remover with 1 part water. Apply liberally over the surface of the tile and agitate with a scrubbing brush. Leave for 5-10 minutes before rinsing with clean water. For extremely stubborn stains, use undiluted Al Fresco Residue Remover and agitate with a scrubbing brush. Always rinse the surface with clean water afterwards.

#### **DIMENSIONS, COLOUR & SHADING**

#### **HEALTH AND SAFETY**

• Always wear gloves and safety footwear.

#### GOODS

#### MAINTENANCE

#### GUARANTEE

#### SLIP RESISTANCE



# Specification





Uniform appearance Pattern, shading and colour differences are



Slight variation Distinguishable yet subtle differences in



### **Guide to Variations**





#### Substantial variation

pattern differences



**Extreme variation**